

AMENDMENTS TO THE CLAIMS

1. (Previously presented) A rotating data storage disk system comprising:
- 5 a plurality of concentric tracks defined on a disk;
- said disk including at least two data storage areas, wherein each area is sized to store a copy of a set of data and the data storage areas are substantially equidistantly spaced from each other and wherein all of the at least two data storage areas are located within plus or minus one track of the
- 10 same track;
- a drive mechanism coupled to the disk;
- an integrated controller that manages data storage operations of the disk system, wherein the integrated controller maintains a first redundant data table in volatile memory, and wherein the first redundant data table
- 15 comprises information about one or more deferred write commands; and,
- a remote controller in communication with the drive mechanism for maintaining data coherency between the at least two data storage areas and keeping track of deferred writes to the at least two data storage areas of the disk, wherein the remote controller maintains a second redundant data table
- 20 in non-volatile memory, wherein the second redundant data table comprises information about one or more deferred write commands.

2. (Original) The rotating data storage disk of claim 1 wherein the at

Lee & Hayes, PLLC

2

HP1-786US
200302135-1

7/19/2005

BEST AVAILABLE COPY

least two data storage areas are located at radially opposed locations at a substantially 180 degree angular offset with respect to a spin axis of the rotating data storage disk and mirrored across the spin axis.

5 3. (Canceled)

4. (Original) The rotating data storage disk of claim 1 wherein the disk further comprises at least two magnetic recording surfaces, wherein the data storage areas are formed in a single one of the at least two magnetic
10 recording surfaces.

5. (Original) The rotating data storage disk of claim 1 wherein the disk further comprises at least two magnetic recording surfaces, wherein the data storage areas are formed in separate ones of the at least two magnetic
15 recording surfaces.

6. (Original) The rotating data storage disk of claim 1 wherein the disk further comprises an optical recording surface.

20 7. (Original) The rotating data storage disk of claim 1 wherein the disk further comprises a magneto-optical recording surface.

8. (Canceled)

Lee & Hayes, PLLC

3

HP1-786US
200302135-1

7/19/2005

BEST AVAILABLE COPY

9. (Canceled)

10. (Previously Presented) The rotating data storage disk of claim 1
5 wherein the at least two data storage areas comprise "n" storage areas and
the disk exhibits a characteristic virtual revolutions per minute (RPM) that is
a multiple n of the actual spin speed of the rotating data storage disk.

11. (Previously presented) A disk drive system comprising:
10 one or more platters, each platter supporting at least one recording
surface, wherein the platters are aligned about a common central axis;
a plurality of concentric tracks defined on the platter;
means for spinning the platters about the common central axis;
a recording head associated with each recording surface;
15 an actuator mechanism coupled to each recording head to move the
recording head into proximity with selected portions of the recording surface
in response to received commands;
at least two replicates of data stored in at least two data storage areas
such that any one of the at least two replicates can be accessed to service a
20 data access request and all of the at least two data storage areas are
located within plus or minus one track of the same track;
an integrated controller that manages data storage operations of the

Lee & Hayes, PLLC

4

HP1-786US
200302135-1

7/18/2005

disk drive system, wherein the integrated controller maintains a first redundant data table in volatile memory, and wherein the first redundant data table comprises information about one or more deferred write commands; and,

- 5 a remote controller for maintaining data coherency between the at least two data storage areas and keeping track of deferred writes to the data storage areas, wherein the remote controller maintains a second redundant data table in non-volatile memory, and wherein the second redundant data table comprises information about one or more deferred write commands.

10

12. (Previously Presented) The disk drive system of claim 11 wherein the data storage areas are located so as to be mirrored about a spin axis of the platters.

- 15 13. (Canceled)

14. (Original) The disk drive system of claim 11 wherein the data storage areas are formed in a single one of the one or more platters.

- 20 15. (Original) The disk drive system of claim 11 wherein the data storage areas are formed in separate platters of the one or more platters.

16. (Previously Presented) The disk drive system of claim 11 wherein

Lee & Hayes, PLLC

5

HP1-788US
200302135-1

7/18/2005

each recording surface further comprises a plurality of concentric tracks defined on the recording surface and each track is substantially aligned with a corresponding track on an adjacent platter, wherein all of the at least two data storage areas are located on adjacent tracks.

5

17. (Canceled)

18. (Currently amended) The disk drive system of claim 11 wherein the at least two data storage areas comprise "n" storage areas and the disk platter exhibits a characteristic virtual revolutions per minute (RPM) that is a multiple n of the actual spin speed of the rotating data storage platter.

19. (Previously Presented) The disk drive system of claim 11 further comprising:

15 a command processor having an interface to receive external disk access requests and coupled to provide the disk access request to the actuator mechanism; and

memory coupled to the command processor and configured to store redundant write access request commands such that the at least two replicates can be stored asynchronously.

20. - 33. (Cancelled).

Lee & Hayes, PLLC

6

HP1-788US
200302135-1

7/18/2005

34. (Previously presented) The disk drive system of claim 1, wherein:
the integrated controller uses the information in the first redundant
data table to perform a deferred write operation to one or more of the at least
5 two data storage areas.

35. (Previously presented) The disk drive system of claim 34 wherein,
upon completion of the deferred write operation, the integrated controller:
removes an entry corresponding to the deferred write operation from
10 the first redundant data table; and
transmits a notification to the remote controller indicating completion
of the deferred write operation.

36. (Previously presented) The disk drive system of claim 35 wherein,
15 upon receipt of the notification, the remote controller removes an entry
corresponding to the deferred write operation from the second redundant
data table.

37. (Previously presented) The disk drive system of claim 1, wherein:
20 In response to a read request from a host computer, the remote
controller uses the second redundant data table to determine whether the
read request references data on the disk drive that is coherent.

Lee & Hayes, PLLC

7

HP1-786US
200302135-1

7/18/2005

38. (Previously presented) The disk drive system of claim 37 wherein the remote controller issues a SCSI read command if the read request references coherent data.

5 39. (Previously presented) The disk drive system of claim 37, wherein the remote controller issues a modified read command if the read request references data that is not coherent, wherein the modified read command specifies a location on the disk drive from which to read the referenced data.

10 40. - 41. (Cancelled).

42. (Previously presented) The disk drive system of claim 11, wherein:

the integrated controller uses the information in the first redundant
15 data table to perform a deferred write operation to one or more of the at least two data storage areas.

43. (Previously presented) The disk drive system of claim 42 wherein, upon completion of the deferred write operation, the integrated controller:
20 removes an entry corresponding to the deferred write operation from the first redundant data table; and

transmits a notification to the remote controller indicating completion of the deferred write operation.

Lee & Hayes, PLLC

8

HP1-786US
200302135-1

7/19/2005

44. (Previously presented) The disk drive system of claim 43 wherein,
upon receipt of the notification, the remote controller removes an entry
corresponding to the deferred write operation from the second redundant
5 data table.

45. (Currently amended) The disk drive system of claim 11, wherein:

in response to a read request from a host computer, the remote
controller uses the second redundant data table to determine whether the
10 read request references data on the disk drive platter that is coherent.

46. (Previously presented) The disk drive system of claim 45 wherein the
remote controller issues a SCSI read command if the read request
references coherent data.

15

47. (Previously presented) The disk drive system of claim 45, wherein the
remote controller issues a modified read command if the read request
references data that is not coherent, wherein the modified read command
specifies a location on the disk drive from which to read the requested data.

Lee & Hayes, PLLC

9

HP1-788US
200302135-1


7/19/2005

BEST AVAILABLE COPY

5

Respectfully Submitted,
Lee & Hayes, PLLC

Dated: 7/18/05



10

Paul W. Mitchell
Lee & Hayes, PLLC
Reg. No. 44,453
(509) 324-9256 x 237

15 Direct correspondence to:
Hewlett-Packard Company
Intellectual Property Administration
P.O. Box 272400
Fort Collins, CO 80527-2400

20

Lee & Hayes, PLLC

10

HP1-786US
200302135-1

7/18/2005